

## **IN THE CLAIMS**

1. (Original)            A receiver device comprising:  
  
a plurality of antennas having different antenna gains;  
  
an antenna switching device for selecting one of reception signals received by the plurality of antennas, and supplying the selected reception signal to a signal processor arranged subsequent to the antenna switching device;  
  
a detector for detecting the level of a reception signal from each antenna;  
  
a controller for controlling the antenna switching device for selecting a reception signal having a lower level than a maximum input level of the signal processor, in accordance with detection result from the detector.
  
2. (Original)            A receiver device according to claim 1,  
  
wherein the controller has a judger for judging a reception state of each antenna;  
  
and  
  
when there are a plurality of antennas capable of receiving signals without any troubles, the antenna switching device is controlled so as to select a reception signal from an antenna having a low antenna gain.
  
3. (Original)            A receiver device according to claim 1,  
  
wherein the plurality of antennas are located close to one another,  
  
wherein the controller operates to control the antenna switching device, in a manner such that once the level of a reception signal supplied to the signal processor approaches a maximum input level of the signal processor, an antenna having a lower antenna gain than that of an antenna being selected is selected.

4. (Original) A receiver device according to claim 1,

wherein the controller operates to control the antenna switching device, in a manner such that once the level of a reception signal supplied to the signal processor becomes lower than a predetermined level, an antenna having a higher antenna gain than that of an antenna being selected is selected.

5. (Original) A receiver device according to claim 1,

wherein the controller operates to control the antenna switching device, in a manner such that once a reception signal of each antenna becomes lower than a predetermined level, a reception signal from an antenna having a high antenna gain is selected, and that when there are plurality of reception signals having a higher level than the predetermined level, a reception signal from an antenna having a low antenna gain is selected.

6. (New) A method for selecting a receiving antenna in a receiving device, comprising:

detecting the level of a reception signal from each antenna in a plurality of antennas;

based on the detection result from the detector, selecting one antenna from the plurality of antennas, the reception signal from the selected antenna having a lower level than a maximum input level of a signal processor; and

supplying the reception signal from the selected antenna to the signal processor.